

# WELUX LED Track Spotlight

## Silber Series

Housing and Trim: Die-cast aluminium  
 Mounting type: Surface  
 Heat Management: Die-cast aluminium heat sink  
 Reflector: Aluminium  
 Beam angle: 12/24/36  
 Diffuser: Clear PMMA

LED Modules  
 GERMAN Technology  
 Comfort COB - Up to 5500lm  
 Long service life time : 50,000 hours (L80/B10)  
 Ambient temperature - 40°C to +40°C

Drivers: 500mA / 700mA / 900mA / 1050mA  
 (optional: Dimmable available)  
 Power factor at full load : 0.97  
 SELV , Low Ripple current < 1% ,THD <15%  
 Warranty: 5 years

Standards  
 EN 620301: LED modules for general lighting - Safety specification  
 EN 62471: Photobiological safety of lamps and systems  
 EN 55015: Radio disturbance emissions  
 EN 61000-3-2 Limited for harmonic emissions  
 EN 61547: Immunity requirements



Powered by:



Application: Commercial Building, Lobby, Conventional Hall, Ballroom, Concourse

Model	System Wattage	Voltage	Frequency	Power Factor	Colour	Colour Temperature	Module Luminous Flux (Lm)	Module Efficacy Lm/W	Typ. Beam Angle	Typ. CRI Ra	Energy Efficiency	Dimension (Dia x H) mm	Dimension (Cut out) mm
ST8-19W	19.5W	220-240	50/60Hz	0.95	Warm white	2700K	2585	149	15°/24°36°	>82	A+	77 x 225	
		220-240	50/60Hz	0.95	Warm white	3000K	2725	158	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	2805	162	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	2860	165	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	2830	164	15°/24°36°	>82	A+		
ST8-27W	27.5W	220-240	50/60Hz	0.95	Warm white	2700K	3445	137	15°/24°36°	>82	A+	85 x 266	
		220-240	50/60Hz	0.95	Warm white	3000K	3625	144	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	3730	148	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	3805	151	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	3765	150	15°/24°36°	>82	A+		
ST8-34W	34.5W	220-240	50/60Hz	0.95	Warm white	2700K	4455	139	15°/24°36°	>82	A+	105 x 280	
		220-240	50/60Hz	0.95	Warm white	3000K	4690	147	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	4830	151	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	4920	154	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	4875	152	15°/24°36°	>82	A+		
ST8-41W	41.0W	220-240	50/60Hz	0.95	Warm white	2700K	5045	133	15°/24°36°	>82	A+	105 x 280	
		220-240	50/60Hz	0.95	Warm white	3000K	5310	140	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	5465	144	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	5575	147	15°/24°36°	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	5520	145	15°/24°36°	>82	A+		

\*Colour tolerance: 3 MacAdam    \*\*Production tolerance of luminous flux and efficiency: ±10%    \*\*\*Min. CRI ±3%    \*\*\*\*Power consumption: ±10%  
 The values contained in this data sheet can change due to technical innovations without notifications, therefore kindly refer to us when during order.